Rehoo INDUSTRIAL





Needle Detector

Designed for textile and garments industrial.

NDH-A FEATURES

- Fashion form.
- ABS-plastic shell.
- 2 Steps sensitivity adjustment (hi or low).
- Power supply:DC3V AA*2, long life.

NDH-A SPECIFICATIONS

Model	NDH-A
Detection method	Magnetic induction
Detection sensitivity	Lo:20-30mm Hi-30-40mm With an iron setting pin of ¢0.7mm, length 25mm, detection is possible within following renges
Detection adjustment	Lo-Hi2steps
Detection width	50*25mm
Alarm method	Buzzer, Lamp
Power source	1.5V battery*2(AA)
Dimension	160mm(L)*55mm(W)*45mm(H)
Weight	Appr200g

NDT-A FEATURES

- ABS-plastic shell.
- Anti-static cover.
- 8 segments Led monitor identifies the exact location of foreign object so that you can find it easily.
- Touch-button integrated control panel.
- 6 steps sensitivity adjustment.
- Designed for universal AC power supply (full range).
- SMD technology.

NDT-A SPECIFICATIONS

Model		NDT-A
Detection method		Magnetic induction
Detection sensitivity	ļ	Max 110mm height by steel needle(⊄ 0.6*L33)
Detection adjustment		6steps
Detection width	Ţ	160*500mm
Alarm method	Ţ	Buzzer, Lamp
Power source	J	AC85-265V 45-65HZ
Rated output	J	Appr10W
Dimension	Ţ	400mm(L)*680mm(W)*70mm(H)
Weight	J	Appr 11Kg

www.rehoo.com.hk